



COMPETITION SPECIFICATION SHEET 7/1/2005

Manufacturer: BMW
Model: 328i/S (E36 2.8L)
Applicable Years: 1994-1999

This specification sheet was developed by the U.S. Touring Car Championship and will be used both by the series technical administrator to establish technical compliance and by applicable series administrators to maintain performance parity and equal competition amongst the USTCC competitors. In addition to this CSS the technical administrator may also use, but is not limited to also using the following items to check compliance: Electronic Parts Catalogs, Technical Information Systems, and the FIA/ASN Homologation forms, or equivalent documentation.

The specifications within this form include all modifications that have been approved by USTCC specifically for the vehicle model(s) and year(s) listed on this page. The parts, specifications and assemblies used shall be those for the unmodified stock vehicle, those permitted within the NASA regulations and or within this CSS. If the stock parts, specifications, and/or assemblies exceed the performance potential of those approved within this form, then the parts, specifications, and/or assemblies used shall meet those listed within this form.

The Competition Specification Sheet is a permissive document. The exact configuration of any modification allowed within this CSS is subject to the approval of the technical administrator.

1. GENERAL VEHICLE DESCRIPTION

Body Type (sedan, coupe, hatchback):	Coupe or Sedan
Engine location (front, mid, rear):	Front
Drive Type (front, rear, AWD):	Rear
Wheelbase (cm)	270.0
Induction Type:	Naturally Aspirated
Minimum Weight:	2750lbs

2. ENGINE

OEM Engine Code Designation:	M52B28
Number of Cylinders:	6
Maximum Displacement (cc):	2793
Rev limit req'd?:	no
Compression ratio:	10.2:1
Piston Stroke (mm):	84.0
Restrictors Req'd?:	no
Cylinder Block Part # (stock):	11.11.1.433.067
Cylinder Block Bore (mm):	84.0
Cylinder Head Part # (stock):	11.12.1.703.637
Intake Valve Head Diameter (mm):	33.0
Exhaust Valve Head Diameter (mm):	30.5

Intake Port Dimensions at Manifold Face:	Height: 24.8mm Width: 54.7mm
Intake Port Work Allowed? (Yes/No)	no
Exhaust Port Dimensions at Manifold Face:	Height: 26.6mm Width: 41.2mm
Exhaust Port Work Allowed? (Yes/No)	no
Connecting Rod Length (centerlines, mm):	140.0
Reciprocating Assembly (grams):	988
Aftermarket Rods Allowed?:	no
Aftermarket Pistons Allowed?:	no
Camshaft Rocker Arm Ratio:	1.0:1
Type of Cam Follower (roller, solid, etc.)	Direct Action
Camshaft Max Lift at Cam Lobe:	0.354" (stock is 9mm I&E)
Crankshaft Part Number (stock):	11.21.1.709.059
Crankshaft Mass (kg):	21.32
Flywheel Mass (kg):	11.36 / open
Ring Gear Diameter (mm):	290
Intake Manifold Part # (stock):	11.61.1.735.727
Int. Manifold Port Size @ Head Face:	Height: 24.8mm Width: 54.7mm (stock)
Allow Port Match to Head?	no
Throttle Body Bore Diameter (mm):	64
# of Throttle Bodies:	1
Intermediate Port Matching Allowed?:	N/A
Turbocharger Manufacturer and Model:	N/A
Alternate Turbocharger Allowed?:	N/A
Number of Turbo Compressors:	N/A
Compressor Inlet Diameter (mm):	N/A
Maximum Boost Pressure (psi):	N/A
Turbo Intercooler Part # (stock):	N/A
Turbo Intercooler Dimensions (mm):	N/A
Engine Miscellaneous: Camshaft P/N:	11311405051 & 11311405488 permitted

3. DRIVETRAIN

Transmission Part # (stock)	BMW ZF 23.00.1.434.485
Number of Forward Speeds:	5
Alternate Transmission Allowed?:	no
Alternate Transmission Part #:	n/a
Gear Ratios (stock / allowed):	
1 st :	4.210
2 nd :	2.490
3 rd :	1.660
4 th :	1.240
5 th :	1.000
6 th :	N/A
Final Drive Ratio (stock / allowed):	3.730 / open
Drivetrain Miscellaneous:	

4. SUSPENSION, CHASSIS, BODY

Front Suspension Type:	MacPherson
Rear Suspension Type:	Multi-Link
Suspension, Chassis, Body Miscellaneous:	